


# HiPerDynFRED

High Performance Dynamic Fast Recovery Diode  
 Extreme Low Loss and Soft Recovery  
 Parallel legs with series connected dice

$V_{RRM} = 1200\text{ V}$   
 $I_{FAV} = 2 \times 25\text{ A}$   
 $t_{rr} = 15\text{ ns}$

Part number

**DSEP2x25-12C**



Backside: isolated

E72873

**Features / Advantages:**

- Planar passivated chips
- Very low leakage current
- Very short recovery time
- Improved thermal behaviour
- Very low  $I_{rm}$ -values
- Very soft recovery behaviour
- Soft reverse recovery for low EMI/RFI
- Low  $I_{rm}$  reduces:
  - Power dissipation within the diode
  - Turn-on loss in the commutating switch

**Applications:**

- Antiparallel diode for high frequency switching devices
- Antisaturation diode
- Snubber diode
- Free wheeling diode
- Rectifiers in switch mode power supplies (SMPS)
- Uninterruptible power supplies (UPS)

**Package:**


- Housing: SOT-227B (minibloc)
- Industry standard outline
- Cu base plate internal DCB isolated
- Isolation Voltage 3000 V
- Epoxy meets UL 94V-0
- RoHS compliant

**Ratings**

| Symbol     | Definition                          | Conditions                              | Ratings                                |      |      | Unit               |   |
|------------|-------------------------------------|---|--|------|------|--------------------|---|
|            |                                     |   | min.                                   | typ. | max. |                    |   |
| $V_{RRM}$  | max. repetitive reverse voltage     | $T_{VJ} = 25\text{ }^{\circ}\text{C}$   |  |      | 1200 | V                  |   |
| $I_R$      | reverse current                     | $V_R = 1200\text{ V}$                   |  |      | 250  | $\mu\text{A}$      |   |
|            |                                     | $V_R = 1200\text{ V}$                   |  |      | 2    | mA                 |   |
| $V_F$      | forward voltage                     | $I_F = 25\text{ A}$                     |  |      | 4.71 | V                  |   |
|            |                                     | $I_F = 50\text{ A}$                     |  |      | 5.92 | V                  |   |
|            |                                     | $I_F = 25\text{ A}$                     | $T_{VJ} = 150\text{ }^{\circ}\text{C}$ |      |      | 2.95               | V |
|            |                                     | $I_F = 50\text{ A}$                     | $T_{VJ} = 150\text{ }^{\circ}\text{C}$ |      |      | 4.01               | V |
| $I_{FAV}$  | average forward current             | rectangular $d = 0.5$                   | $T_C = 90\text{ }^{\circ}\text{C}$     |      | 25   | A                  |   |
| $V_{F0}$   | threshold voltage                   | } for power loss calculation only       | $T_{VJ} = 150\text{ }^{\circ}\text{C}$ |      | 1.95 | V                  |   |
| $r_F$      | slope resistance                    |   |  |      | 40   | m $\Omega$         |   |
| $R_{thJC}$ | thermal resistance junction to case |   |  |      | 0.60 | K/W                |   |
| $T_{VJ}$   | virtual junction temperature        |   | -40                                    |      | 150  | $^{\circ}\text{C}$ |   |
| $P_{tot}$  | total power dissipation             |   | $T_C = 25\text{ }^{\circ}\text{C}$     |      | 210  | W                  |   |
| $I_{FSM}$  | max. forward surge current          | $t = 10\text{ ms}$ (50 Hz), sine        | $T_{VJ} = 45\text{ }^{\circ}\text{C}$  |      | 250  | A                  |   |
| $I_{RM}$   | max. reverse recovery current       |   | $T_{VJ} = 25\text{ }^{\circ}\text{C}$  |      | 5.5  | A                  |   |
|            |                                     | $I_F = 30\text{ A}; V_R = 600\text{ V}$ | $T_{VJ} = 100\text{ }^{\circ}\text{C}$ |      | 12.5 | A                  |   |
| $t_{rr}$   | reverse recovery time               | $-di_F/dt = 600\text{ A}/\mu\text{s}$   | $T_{VJ} = 25\text{ }^{\circ}\text{C}$  |      | 15   | ns                 |   |
|            |                                     |   | $T_{VJ} = 100\text{ }^{\circ}\text{C}$ |      | 70   | ns                 |   |
| $C_J$      | junction capacitance                | $V_R = 400\text{ V}; f = 1\text{ MHz}$  | $T_{VJ} = 25\text{ }^{\circ}\text{C}$  |      | 18   | pF                 |   |


| Symbol        | Definition  | Conditions           | Ratings |      |      | Unit |
|---------------|---|----------------------|---------|------|------|------|
|               |   |                      | min.    | typ. | max. |      |
| $I_{RMS}$     | RMS current   | per terminal         |         |      | 100  | A    |
| $R_{thCH}$    | thermal resistance case to heatsink                   |                      |         | 0.10 |      | K/W  |
| $T_{stg}$     | storage temperature                                   |                      | -40     |      | 150  | °C   |
| <b>Weight</b> |   |                      |         | 30   |      | g    |
| $M_D$         | mounting torque                                       |                      | 1.1     |      | 1.5  | Nm   |
| $M_T$         | terminal torque                                       |                      | 1.1     |      | 1.5  | Nm   |
| $V_{ISOL}$    | isolation voltage                                     | t = 1 second         | 3000    |      |      | V    |
|               |   | t = 1 minute         | 2500    |      |      | V    |
| $d_{Spp/APP}$ | creepage   striking distance on surface   through air | terminal to terminal | 10.5    | 3.3  |      | mm   |
| $d_{Spb/APb}$ | creepage   striking distance on surface   through air | terminal to backside | 8.8     | 6.9  |      | mm   |

### Product Marking



| Ordering | Part Name    | Marking on Product | Delivering Mode | Base Qty | Code Key |
|----------|--------------|--------------------|-----------------|----------|----------|
| Standard | DSEP2x25-12C | DSEP2x25-12C       | Tube            | 10       | 482021   |

Outlines SOT-227B (minibloc)



| SYM | MILLIMETERS |       | INCHES |       |
|-----|-------------|-------|--------|-------|
|     | MIN         | MAX   | MIN    | MAX   |
| A   | 31.50       | 31.88 | 1.240  | 1.255 |
| B   | 7.80        | 8.20  | .307   | .323  |
| C   | 4.09        | 4.29  | .161   | .169  |
| D   | 4.09        | 4.29  | .161   | .169  |
| E   | 4.09        | 4.29  | .161   | .169  |
| F   | 14.91       | 15.11 | .587   | .595  |
| G   | 30.12       | 30.30 | 1.186  | 1.193 |
| H   | 37.80       | 38.23 | 1.489  | 1.505 |
| J   | 11.68       | 12.22 | .460   | .481  |
| K   | 8.92        | 9.60  | .351   | .378  |
| L   | 0.76        | 0.84  | .030   | .033  |
| M   | 12.60       | 12.85 | .496   | .506  |
| N   | 25.15       | 25.42 | .990   | 1.001 |
| O   | 1.98        | 2.13  | .078   | .084  |
| P   | 4.95        | 5.97  | .195   | .235  |
| Q   | 26.54       | 26.90 | 1.045  | 1.059 |
| R   | 3.94        | 4.42  | .155   | .174  |
| S   | 4.72        | 4.85  | .186   | .191  |
| T   | 24.59       | 25.07 | .968   | .987  |
| U   | -.05        | .10   | -.002  | .004  |
| V   | 3.30        | 4.57  | .130   | .180  |
| W   | 19.81       | 21.08 | .780   | .830  |




Fig. 1 Forward current  $I_F$  vs.  $V_F$




Fig. 2 Reverse recovery charge  $Q_r$  versus  $-di_F/dt$




Fig. 3 Peak reverse current  $I_{RM}$  versus  $-di_F/dt$




Fig. 4 Dynamic parameters  $Q_r$ ,  $I_{RM}$  versus  $T_{VJ}$




Fig. 5 Recovery time  $t_{tr}$  versus  $-di_F/dt$




Fig. 6 Peak forward voltage  $V_{FR}$  and  $t_{fr}$  versus  $di_F/dt$




Fig. 7 Transient thermal resistance junction to case

Constants for  $Z_{thJC}$  calculation:

| i | $R_{thi}$ (K/W) | $t_i$ (s) |
|---|-----------------|-----------|
| 1 | 0.037           | 0.00024   |
| 2 | 0.07            | 0.0036    |
| 3 | 0.246           | 0.0235    |
| 4 | 0.176           | 0.142     |
| 5 | 0.07            | 0.7       |