


## Power Schottky Rectifier with common cathode

$$I_{FAV} = 2 \times 20 \text{ A}$$


$$V_{RRM} = 60 \text{ V}$$

$$V_F = 0.50 \text{ V}$$

$V_{RSM}$	$V_{RRM}$	Type
V	V	
60	60	DSSK 40-006B



TO-247 AD



A = Anode, C = Cathode, TAB = Cathode

Symbol	Conditions	Maximum Ratings	
$I_{FRMS}$		70	A
$I_{FAV}$	$T_C = 130^\circ\text{C}$ ; rectangular, $d = 0.5$	20	A
$I_{FAV}$	$T_C = 130^\circ\text{C}$ ; rectangular, $d = 0.5$ ; per device	40	A
$I_{FSM}$	$T_{VJ} = 45^\circ\text{C}$ ; $t_p = 10 \text{ ms}$ (50 Hz), sine	500	A
$E_{AS}$	$I_{AS} = \text{tbd A}$ ; $L = 180 \mu\text{H}$ ; $T_{VJ} = 25^\circ\text{C}$ ; non repetitive	tbd	mJ
$I_{AR}$	$V_A = 1.5 \cdot V_{RRM}$ typ.; $f = 10 \text{ kHz}$ ; repetitive	tbd	A
$(dv/dt)_{cr}$		tbd	V/ $\mu\text{s}$
$T_{VJ}$		-55...+150	$^\circ\text{C}$
$T_{VJM}$		150	$^\circ\text{C}$
$T_{stg}$		-55...+150	$^\circ\text{C}$
$P_{tot}$	$T_C = 25^\circ\text{C}$	150	W
$M_d$	mounting torque	0.8...1.2	Nm
Weight	typical	6	g

### Features

- International standard package
- Very low  $V_F$
- Extremely low switching losses
- Low  $I_{RM}$ -values
- Epoxy meets UL 94V-0

### Applications

- Rectifiers in switch mode power supplies (SMPS)
- Free wheeling diode in low voltage converters

### Advantages

- High reliability circuit operation
- Low voltage peaks for reduced protection circuits
- Low noise switching
- Low losses

Dimensions see outlines.pdf

Symbol	Conditions	Characteristic Values	
		typ.	max.
$I_R$ ①	$T_{VJ} = 25^\circ\text{C}$ $V_R = V_{RRM}$		20 mA
	$T_{VJ} = 100^\circ\text{C}$ $V_R = V_{RRM}$		175 mA
$V_F$	$I_F = 20 \text{ A}$ ; $T_{VJ} = 125^\circ\text{C}$		0.50 V
	$I_F = 20 \text{ A}$ ; $T_{VJ} = 25^\circ\text{C}$		0.53 V
	$I_F = 40 \text{ A}$ ; $T_{VJ} = 125^\circ\text{C}$		0.60 V
$R_{thJC}$			1.1 K/W
$R_{thCH}$	0.25		K/W

Pulse test: ① Pulse Width = 5 ms, Duty Cycle < 2.0 %  
Data according to IEC 60747 and per diode unless otherwise specified

IXYS reserves the right to change limits, Conditions and dimensions.